



NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~18GHz
3	V.S.W.R	1.25 Max
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	AC 1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	Center contact ≤ 3.0mΩ Outer contact ≤ 2.0mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Durability	500 Matings
11	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Gold
2	Contact	BeCu	Gold
3	Insulator	Teflon	-
4	Nut	Brass	Gold
5	Washer	Brass	Gold

Dimensions Are in Millimeters  
Unless Otherwise Specified  
Tolerances

0.5-6 = ± 0.2  
6-30 = ± 0.4  
30-120 = ± 0.6  
120-315 = ± 1.0  
315-1000 = ± 1.6  
1000-2000 = ± 2.4

**ROHS COMPLIANT**

**COSMTEC** COSMTEC RESOURCES CO., LTD

DRAFT      CHECKED      APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd  
And Should Not Be Used Without Written Permission.  
Specifications are subject to change without prior notice. Cosmtec Resource Co., Ltd  
All Rights Reserved, E & OE      www.cosmtec.com

Part No.	S-036-10		
Title:	SMA JACK SOLDER FOR PCB T.G.G. (LONG THREAD)		
DATE:	SCALE:	UNIT	REV
MAY/03/2017	1:1	m/m	A