




NO	Items	Specs
1	Impedance	50 Ω
2	Frequency	DC~6GHz
3	Working Voltage	335V rms
4	Dielectric Withstanding Voltage	1000V rms
5	Insulation Resistance	1G Ω Min
6	Contact Resistance	Center contact $\leq 5.0m\Omega$ Outer contact $\leq 2.5m\Omega$
7	Temperature Range	-55°C ~ +165°C
8	Mating	Snap-On
9	Durability	500 Matings
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Shell	Brass	Gold
2	Body	Brass	Gold
3	Contact	P.H. Bronze	Gold
4	Body	Brass	Gold
5	Snap Ring	BeCu	—
6	Insulator	Teflon	—
7	Ferrule	Brass	Gold

Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances



0.5-6 = ± 0.2
6-30 = ± 0.4
30-120 = ± 0.6
120-315 = ± 1.0
315-1000 = ± 1.6
1000-2000 = ± 2.4



COSMTEC RESOURCES CO., LTD

DRAFT

CHECKED

APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission.
Specifications are subject to change without prior notice. Cosmtec Resource Co., Ltd
All Rights Reserved, E & OE
www.cosmtec.com

Part No. SB-001-316-TGG

Title: SMB PLUG (FEMALE PIN) CRIMP
FOR RG-174/316

DATE: DEC/04/2017 SCALE: 1:1 UNIT: m/m REV: A