



NO	Description	Material	Finish
1	Body	Brass	CuSnZn
2	Ground	P.H Bronze	CuSnZn
3	Contact	P.H Bronze	CuSnZn
4	Shell	Brass	CuSnZn
5	Snap Ring	SUS304	-
6	Insulator	Teflon	-
7	Ground Tube	Brass	CuSnZn
8	Gasket	Silicone	-

Dimensions Are In Millimeters
Unless Otherwise Specified
Tolerances

0.5-6 = ± 0.2
6-30 = ± 0.4
30-120 = ± 0.6
120-315 = ± 1.0
315-1000 = ± 1.6
1000-2000 = ± 2.4



COSMTEC RESOURCES CO., LTD

DRAFT	CHECKED	APPROVED
-------	---------	----------

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd And Should Not Be Used Without Written Permission. www.cosmtec.com

NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~6GHz
3	V.S.W.R	1.20 Max
4	PIM	-155dBc Max.
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	1500V
6	Insulation Resistance	3000 MΩ Min
7	Contact Resistance	Center contact ≤ 2mΩ Outer contact ≤ 1mΩ
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On / 500 Cycles
10	Material/Finish	All RoHS Compliant

Part No. MMN-011

Title: 2.2-5 JACK TO N PLUG ADAPTER

DATE: AUG/01/2022	SCALE: 1:1	UNIT: m/m	REV: A
-------------------	------------	-----------	--------