



NO	Items	Specs
1	Impedance	50Ω
2	Frequency	DC~6GHz
3	V.S.W.R	1.20 Max
4	PIM	-155dBc Max.
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	1500V
6	Insulation Resistance	3000 MΩ Min
7	Contact Resistance	Center contact ≤ 2mΩ Outer contact ≤ 1mΩ
8	Temperture Range	-55°C ~ +165°C
9	Mating	Screw-On / 500 Cycles
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	CuSnZn
2	Body	Brass	CuSnZn
3	Insulator	Teflon	-
4	Contactator	P.H Bronze	CuSnZn

*Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances*

0.5-6	= ± 0.2
6-30	= ± 0.4
30-120	= ± 0.6
120-315	= ± 1.0
315-1000	= ± 1.6
1000-2000	= ± 2.4

ROHS COMPLIANT

COSMTEC **COSMTEC RESOURCES CO.,LTD**

DRAFT CHECKED APPROVED

The Drawing Contans Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No.	MMN-014			
Title:	2.2-5 JACK TO PLUG ADAPTER			
DATE:	SEP/07/2022	SCALE:	1:1	UNIT
			m/m	REV
				A