



NO	Items	Specs
1	Impedance	50 Ω
2	Frequency	DC~18 GHz
3	V.S.W.R	1.2 Max
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	AC 1500V
6	Insulation Resistance	5000 M Ω Min
7	Contact Resistance	Center contact \leq 3.0m Ω Outer contact \leq 2.0m Ω
8	Temperture Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Ground Cover	Brass	Nickel
4	Insulator	Teflon	-
5	Contactors	P.H Bronze	Gold

Dimensions Are in Millimeters
 Unless Otherwise Specified
 Tolerances

0.5-6 = \pm 0.2
 6-30 = \pm 0.4
 30-120 = \pm 0.6
 120-315 = \pm 1.0
 315-1000 = \pm 1.6
 1000-2000 = \pm 2.4

ROHS COMPLIANT



COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
 And Should Not Be Used Without Written Permission. www.cosmtec.com

Part No. N-034

Title: N JACK TO JACK ADAPTER
 FLANGE MOUNT 4 HOLES ONE BODY

DATE: MAR/03/2020 SCALE: 1:1 UNIT m/m REV A