



NO	Description	Material	Finish
1	Body	Brass	Nickel
2	Insulator	Teflon	-
3	Contactors	Brass	Gold
4	Body	Brass	Nickel
5	Contactors	P.H Bronze	Gold
6	Shell	Brass	Nickel
7	Snap Ring	Brass	-

Dimensions Are in Millimeters
Unless Otherwise Specified
Tolerances

0.5-6 = ± 0.2
6-30 = ± 0.4
30-120 = ± 0.6
120-315 = ± 1.0
315-1000 = ± 1.6
1000-2000 = ± 2.4



COSMTEC COSMTEC RESOURCES CO., LTD

DRAFT CHECKED APPROVED

The Drawing Contains Information That Is Proprietary To Cosmtec Resources Co., Ltd
And Should Not Be Used Without Written Permission. www.cosmtec.com

NO	Items	Specs
1	Impedance	-
2	Frequency	DC~300MHz
3	V.S.W.R	-
4	Working Voltage	500V
5	Dielectric Withstanding Voltage	1500V
6	Insulation Resistance	5000 MΩ Min
7	Contact Resistance	-
8	Temperature Range	-55°C ~ +165°C
9	Mating	Screw-On
10	Material/Finish	All RoHS Compliant

Part No.	S-017 (M-TYPE)		
Title:	SMA JACK-UNF PLUG ADAPTER (M16P1.0)		
DATE:	MAY/04/2022	SCALE:	1:1
UNIT	m/m	REV	A